

NATIONAL WOOD PRESERVATIVE DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL WOOD PRESERVATIVE	
PRODUCT DESCRIPTION	National Wood Preservative is a solution containing broad microbiological activity spectrum biocide, which inhibits the growth of algae. It acts against blue stain fungi, brown red fungi, and wood destroying insects. In general product is useful as a wood preservative.
RECOMMENDED USES For preservation of wood, wooden articles from algae, blue stain and general types of wood destroying insects.	

TECHNICAL DATA

COLOUR, DRY FILM	Liquid
FINISH, DRY FILM	Clear, Transparent
SPECIFIC GRAVITY	0.80 ± 0.05
THEORETICAL SPREADING	15 M ² /LTR, indicative, depends on the nature of wood
FLASH POINT	38°C

DRYING TIME

Drying time @ 30 ℃ (Temperature, humidity, air movement, film thickness and number of coats	
all affect the drying time.)	
TOUCH DRY	5 – 10 minutes
DRY TO OVER COAT	1 hour

ADVANTAGES

NATIONAL WOOD	Easy to apply on wooden surface, uniform spreading on
PRESERVATIVE SYSTEM	surface, does not give any colour to surface, can be overcoated
	easily.

APPLICATION INSTRUCTION

SURFACE PREPARATION	Before application, the surface should be sound, clean and free
	from oil, grease, loose particles, dust, etc. Application can be
	done by the recommended application methods.

APPLICATION DATA

APPLICATION METHOD	Brush, cotton cloth wiping.
CLEANING/THINNING	National G.P. Thinner
THINNER (VOLUME)	Ready to use
CONV. SPRAY REQUIREMENTS	Not recommended
NOZZLE SIZE	NA

Rev. 07/18 Page 1/2 ISO 9001 & 14001 OHSAS 18001 CERTIFIED FACTORY



NATIONAL WOOD PRESERVATIVE DECORATIVE COATINGS

TECHNICAL DATA SHEET

SYSTEM

	For wooden surface:
RECOMMENDED SYSTEM	Remove oil or grease from the wooden surface.
To be applied on prepared surface.	If required, sanding can be done, using suitable sand paper to
Apply on dry surface moisture less than	make the surface uniform.
4%.	- Remove loose particles.
	- Apply two coats of wood preservatives, with 30
	minutes interval in each coat.

ADDITIONAL DATA

SHELF LIFE @ 30°C	6 months, in original sealed container, with proper storage
	conditions.

HEALTH & SAFETY

~	
SAFETY	As a general rule, avoid skin and eye contact by wearing
PRECAUTIONS	overalls, gloves, goggles, and mask etc. Spillage on skin should
	immediately be removed by thorough washing with water and
	soap or suitable cleaner. Eye should be flushed with fresh
	water. Avoid inhalation of vapours and paint mist by wearing
	suitable mask. In the event of ingestion and eye contact, seek
	medical attention immediately. Painting must be carried out in
	well-ventilated area.
	This product contains flammable materials and should be kept
	away from the sparks and open flames, smoking in the area
	should not be permitted. Local safety regulations should be
	followed.

STORAGE & HANDLING

STORAGE	Store the paint in proper storage conditions as per the local
	regulations. Keep the paint container in sealed condition under
	shed, away from direct sunlight and extreme temperatures. Do
	not stock paint material near to any ignition sources. Do not put
	back the half or unused material back in original container,
	containing the supplied paint, to avoid contamination. Handle
	with care. Stir well before use. Keep away from the reach of
	children.

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

This data sheet supersedes all previous issued. Issued: 0718

Rev. 07/18 Page 2/2

www.national-paints.com

ISO 9001 & 14001 OHSAS 18001 CERTIFIED FACTORY