

NATIONAL N.C. GOLD
DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL N.C. GOLD	
PRODUCT A fast drying nitrocellulose based topcoat with distinct brillia metallic golden colour. Gives rich finish, which is durable ar weather resistant. Easy to apply on various surfaces.	
RECOMMENDED USES	As a finish paint for industrial and decorative applications. Also suitable for wooden and metal furniture. For further protection and glossy effect, it can be over coated with N.C. Clear Lacquer.

TECHNICAL DATA

COLOUR, DRY FILM	Golden Metallic
FINISH, DRY FILM	Metallic lusture / Glossy
VOLUME SOLIDS	$28 \pm 2\%$
(ASTM D2697)	
SPECIFIC GRAVITY	1.00 ± 0.05
THEORETICAL SPREADING	$14-9 \text{ M}^2/\text{LTR}$
RECOMMENDED DFT (DRY	20 – 30 Microns/Coat
FILM)	
RECOMMENDED WFT (WET	70 – 110 Microns/Coat
FILM)	
FLASH POINT	7°C

DRYING TIME

Drying time @ 30 ℃ (Temperature, humidity, air movement, film thickness and number of coats	
all affect the drying time.)	
TOUCH DRY	15 – 30 minutes
DRY TO RECOAT	3 – 4 hours
HARD DRY	8 – 15 hours

ADVANTAGES

NATIONAL N.C. GOLD	Easy to apply on wooden and metallic surface, for giving
	Golden metallic appearance. Protects and decorates the surface.

APPLICATION INSTRUCTION

SURFACE PREPARATION	Before application, the surface should be sound, clean and free
	from oil, grease, loose particles, dust, etc. Application can be
	done by the recommended application methods.



NATIONAL N.C. GOLD
DECORATIVE COATINGS

TECHNICAL DATA SHEET

APPLICATION DATA

APPLICATION METHOD	Spray
CLEANING/THINNING	National Lacquer Thinner
THINNER (VOLUME)	20 – 30%
CONV. SPRAY REQUIREMENTS	Possible
AIRLESS SPRAY	Pressure : 2000 – 2200 psi
REQUIREMENTS	
NOZZLE SIZE	0.013" – 0.020"
MIXING RATIO (BY VOLUME)	NA
POT LIFE @ 30°c (100 ml)	NA

SYSTEM

RECOMMENDED SYSTEM To be applied on prepared surface.	National N.C. Primer Surfacer	:	1 coat
	National N.C. Putty or Polyester Putty	:	1 coat
	National N.C. Primer Surfacer	:	1 coat
	National N.C. Gold	:	2 coats
	National N.C. Auto Lacquer Clear	:	1 coat

ADDITIONAL DATA

SHELF LIFE @ 30°C	Maximum 6 months, in original sealed container, with proper
	storage conditions.

HEALTH & SAFETY

SAFETY	As a general rule, avoid skin and eye contact by wearing	
PRECAUTIONS	overalls, gloves, goggles, and mask etc. Spillage on skin shoul	
	immediately be removed by thorough washing with water and	
	soap or suitable cleaner. Eye should be flushed with fresh	
	water. Avoid inhalation of vapours and paint mist by wearing	
	suitable mask. In the event of ingestion and eye contact, seek	
	medical attention immediately. Painting must be carried out in	
	well-ventilated area.	
	This product contains flammable materials and should be kept	
	away from the sparks and open flames, smoking in the area	
	should not be permitted. Local safety regulations should be	
	followed.	



NATIONAL N.C. GOLD
DECORATIVE COATINGS

TECHNICAL DATA SHEET

STORAGE & HANDLING

STORAGE	Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not stock paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied point to avoid contamination. Handle
	containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data

This data sheet supersedes all previous issued. Issued: 0718