



NATIONAL GLAZE COAT CLEAR
DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL GLAZE COAT CLEAR

PRODUCT DESCRIPTION	National Glaze Coat Clear is an acrylic co-polymer based clear transparent coating to add sheen on the coloured base coat. It has very good adhesion and low dirt pick up properties. It improves the richness of the surface, with a silky appearance. It contains anti fungal and anti bacterial additives.
----------------------------	---

RECOMMENDED USES	National Glaze Coat Clear is recommend as a topcoat clear for coloured surfaces. It improves the richness and adds a silky finish. National Glaze Coat Clear application reduces the dirt pick up on surfaces. It is recommended for the interior applications.
-------------------------	---

TECHNICAL DATA

COLOUR, DRY FILM	Clear
FINISH, DRY FILM	Transparent/Silky
VOLUME SOLIDS (ASTM D2697)	25 ± 2%
SPECIFIC GRAVITY	1.02 ± 0.05
THEORETICAL SPREADING	25 – 12.5 M ² /LTR
RECOMMENDED DFT (DRY FILM)	10 – 20 Microns/Coat
RECOMMENDED WFT (WET FILM)	40 – 80 Microns/Coat
FLASH POINT	Water Base

DRYING TIME

Drying time @ 30 °C (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.)	
TOUCH DRY	30 – 45 minutes
DRY TO RECOAT	3 – 4 hours
DRY TO OVER COAT	24 hours

ADVANTAGES

NATIONAL GLAZE COAT CLEAR SYSTEM	Adds extra protection to the base coat, low dirt pick up, improves the richness and adds a silky appearance, very good adhesion.
---	--



NATIONAL GLAZE COAT CLEAR
DECORATIVE COATINGS

TECHNICAL DATA SHEET

APPLICATION INSTRUCTION

SURFACE PREPARATION	Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.
----------------------------	---

APPLICATION DATA

APPLICATION METHOD	Roller, Brush or Spray
CLEANING/THINNING	Water
THINNER (VOLUME)	Ready for use
CONV. SPRAY REQUIREMENTS	Possible

SYSTEM

RECOMMENDED SYSTEM To be applied on prepared surface.	National Glaze Coat Clear : 1 – 2 coats
	on following system or any other National recommended system
	National Texture Coatings /
	National Stone Finishes.

ADDITIONAL DATA

SHELF LIFE @ 30°C	12 months, in original sealed container, with proper storage conditions.
--------------------------	--

HEALTH & SAFETY

SAFETY PRECAUTIONS	Generally, most of the water base paints are quite safe to handle with due precautions. As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in well-ventilated area. Local safety regulations to be followed.
---------------------------	--



NATIONAL GLAZE COAT CLEAR
DECORATIVE COATINGS

TECHNICAL DATA SHEET

STORAGE & HANDLING

STORAGE	Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not keep paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.
----------------	---

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests.
We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

This data sheet supersedes all previous issued.
Issued: 0718