



# TECHNICAL DATA SHEET

# (Professional Use Only)

# **GRAVEL GUARD (GOMA)**

#### PRODUCT DESCRIPTION

## **FEATURES**

A special resin blend base undercoat which gives a tough textured undercoat to the refinishing that gives extra protection against stone and gravel chipping. Has good color retention, high resistance to severe weather conditions, good durability and flexibility.

- 01. To coarse texture.
- 02. High Coverage.
- 03. Corrosion and abrasion resistance.

#### **RECOMMENDED USE:**

For refinishing plastisol area on cars as replacement coating.

### **Technical Information**

Colors	White, Black.
Finish	Matt textured.
Viscosity (25°C)	10- 12 Poise.
Specific Gravity	$1.40 \pm 0.10$
Solid by Weight %	$65 \pm 5\%$
Theoretical Spreading Rate	5 - 10 m2/Lit.
Film Thickness	(Dry Film) 100 microns
Impact resistance (25 cm)	Pass
Scratch resistance	Pass
Bending test (15 mm)	Pass
Water resistance (24 Hrs Spot Test	Pass
Flash Point	Approx. 4°C
Volatile organic compounds (VOC)	322.0 gm/liter

#### APPLICATION DATA AND SURFACE PREPARATION

- 1 Remove all rust scale oil and grease from surfaces to be coated. Surface must be clean and dry.
- 2 -May be applied to bare or primed metal.
- 3 -Note: If applying to composite plastic as a sound deadening material sand the composite surface with Numix plastic Primer prior to applying undercoating this will increase adhesion.
- 4 -Hold the gun 6-9 inches from the surface and apply a uniform coat. Allow product to try 3-5 minutes if required apply a second coat.
- 5 Special spray gun.
- 6 -Ready for use, could be diluted with Synthetic Thinner.
- 7 **Note:** Guiding Data for Airless Spray Nozzle Tip: 0.015"-0.20" Nozzle Pressure: 2200 P.S.I





#### MISCELLANEOUS DATA

The product must be stored according to National Regulations. The product should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed. **STORAGE** 

SAFETY / Ensure good ventilation during application and drying. **HEALTH** 

Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a

recognized skin cleaner.

Keep out of reach of children.