

TECHNICAL DATA SHEET

(Professional Use Only)

NUMIX 2K THINNERS

PRODUCT DESCRIPTION

Specially formulated thinner for acrylic Polyurethane coating application. It contains Organic Volatile Solvents.

FEATURES

01. Universal solvents for 1K & 2K Numix Products.
02. The tendency from extra-slow to slow Slow to fast evaporation.
03. In conjunctions with Numix products Gives better flow during application

RECOMMENDED USE:

For car refinish coating application at the prevailing temperature.

Technical Information

Colors	Transparent
Viscosity (25°C)	15 - 20 sec.
Specific Gravity	0.87 - 0.89
Evaporation Rate	5 - 15 min.
Flash Point	25 - 54°C
Mixing Ratio	5-100%

Selection of Thinner

Fast 202	Medium Slow 204	Extra slow 206
For spot repairs or for complete re-spray provided the temperature range bellow 20°C	For the treatment of four to five vehicles panels and the temperature range 25-30 °C	For the treatment of full vehicles panels and the temperature range 30-40 °C

MISCELLANEOUS DATA

STORAGE

The product must be stored according to National Regulations. The product should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.

SAFETY / HEALTH

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. Keep out of reach of children.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.